

Twin Jack Stand Model 300 (Part No. TL13130)

The Trilift® Twin Jack Stand Model 300 is a versatile, heavy duty jack and stand designed to lift and support heavy earth moving equipment such as dozers and trucks to a combined working load limit of 300 tonne. By simply removing the centre carriage each turret can be used as a Single Jack Stand Model 150 (Part No. TL13001).

The inclusion of a locking mechanism ensures compliance with Australian/New Zealand Standard AS/NZS2538-1995, Vehicle Support Stands. Once the load is raised, spring loaded jaws lock into the teeth on either side of the jack transforming the Twin Jack Stands into certified support stands. This feature eliminates the difficult and dangerous procedure of making the change from a jack to a support stand.



Single Jack Model 150 with
Turret and Adaptor



Power

To complement the Trilift® Twin Jack Stand Model 300 we have developed Power Packs allowing the operator to jack both turrets simultaneously or individually.

By way of a quick coupler the power pack and control assembly can be disconnected and reconnected to additional tooling.

Like the Jack Stands the Power Packs can be moved with a pallet jack, hydraulic lift or a powered transport trolley (Part No. TL13250).



Electric Power Packs (Part No. CP03011)
& Pneumatic Power Packs (Part No. CP03015)

Features and Benefits

- Jack and certified Work Stand combined in a single unit
- Adjustable jack widths using centre carriage
- Self-engaging locking jaws for increased safety
- Easy placement under a vehicle using a pallet jack
- Simple release of jaws prior to load lowering
- User friendly, providing maintenance personnel with the confidence to perform their work on equipment with increased stability and safety

Key Operating Data

	SINGLE	TWIN
Working Load Limit	150t	300t
Tare Weight	650kg/1433lbs	1800kg/3968lbs

Key Dimensions

A-B Jack Height (Retracted - Extended)	510 - 840mm	20 - 33in
C-D Adaptor 1	587 - 917mm	23 - 36in
E-F Adaptor 2	812 - 1142mm	32 - 45in
G-H Adaptor 3	887 - 1217mm	35 - 48in
I-J Adaptor 4	962 - 1292mm	38 - 51in
K-L Adaptor 5	1327 - 1733mm	52 - 68in
M 150T/300T Twin Jack Length	700mm	28in
N 150T Jack Width	750mm	30in
O Pallet Jack Tyne-Width	525mm	21in
P-Q 300T Twin Jack Turret Width (Retracted - Extended)	1620 - 1980mm	64 - 78in
R-S 300T Twin Jack Overall Width (Retracted - Extended)	2370 - 2730mm	93 - 107in

Adaptor jacking heights

Each Jack is supplied with adaptors to achieve various lifting heights to a maximum of 1733mm. Custom adaptors are available upon request. With the use of the Turret and Adaptors - 5 additional height adjustments are available.

