

# VWT Jig Universal Spider Tool

(Part No. TL02028)

The hydraulically operated Trilift® Spider Tool is manufactured to bolt onto the Trilift® Variable Work Table range of products. It is designed to assist with the safe and efficient removal and replacement of components such as dozer high drives, differentials and the front hub assemblies of most makes and models of heavy haul trucks.

## Specifications

The Trilift® Universal Spider Tool is compliant with the following standards:

- AS 3990:1993 - Mechanical Equipment Steelwork
- AS/NZS 1554.1:2011 - Structural Steel Welding
- AS 1418.1:2002 - Cranes, Hoists and Winches
- AS/NZS 3678:2011 Hot-rolled plates, floor plates and slabs
- AS/NZS 3679.1:2010 Structural steel - Hot-rolled bars and sections
- AS/NZS 1163:2009 Cold formed structural steel hollow sections
- AS/NZS 1252:1996 High strength steel bolts with associated nuts and washers for structural engineering



### Key Operating Data

Working Load Limit	7716 lbs	3500 kgs
Tare Weight	2094 lbs	950 kgs

### Features and Benefits

- Adjustable to suit various components
- Forklift tine pockets and lifting lugs for ease of handling
- Hydraulically operated
- Integrates with existing Trilift® VWT hydraulics
- Integrates with Trilift® VWT XC20/25/30 remote control

### Key Dimensions (approximately)

A	Length	116in	2943mm
B	Width	55in	1400mm
C	Height	82in	2090mm
D	Tyne Pocket Width	59in	1500mm

